



(43) International Publication Date
7 March 2002 (07.03.2002)

PCT

(10) International Publication Number
WO 02/19147 A1


- (51) International Patent Classification?: G06F 17/00
- (21) International Application Number: PCT/US01/26841
- (22) International Filing Date: 28 August 2001 (28.08.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/228,837 28 August 2000 (28.08.2000) US
- (71) Applicant (*for all designated States except US*): EMOTION, INC. [US/US]; 2600 Park Tower Drive, suite 600, Vienna, VA 22180 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): FLANK, Sharon [US/US]; eMotion, Inc., 2600 Park Tower Drive, Vienna, VA 22180 (US). SPERER, Ruth [IL/IL]; Ha'Shoftim

7, Apt. 45, 46447 Hertzlia (IL). **FORBES, David**, Ian [US/US]; 2851 Woodlawn Avenue, Falls Church, VA 22041 (US). **KLEIN, Ed** [US/US]; eMotion, Inc., 2600 Park Tower Drive, Vienna, VA 22180 (US). **ST. JEAN, Randy** [US/US]; eMotion, Inc., 2600 Park Tower Drive, Vienna, VA 22180 (US). **ROMER, Donna** [US/US]; 2111 Welch St #B-301, Houston, TX 77019 (US). **ROTHEY, James** [US/US]; 5542 Falmead Road, Fairfax, VA 22032 (US). **GRIFFIN, Robert** [US/US]; eMotion, Inc., 2600 Park Tower Drive, Vienna, VA 22180 (US). **SIMONSEN, Keith** [US/US]; 632 Massachusetts Ave NE #1, Washington, DC 20002 (US). **EHLERS, Gerald** [US/US]; eMotion, Inc., 2600 Park Tower Drive, Vienna, VA 22180 (US).

- (74) Agent: OPPEDAHN, Carl; Oppedahl & Larson LLP, P.O. Box 5068, Dillon, CO 80435-5068 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU.

[Continued on next page]

- (54) Title: METHOD AND APPARATUS FOR DIGITAL MEDIA MANAGEMENT, RETRIEVAL, AND COLLABORATION



(57) **Abstract:** The software according to the invention incorporates a glossary management tool (fig. 2) that makes it easy for each client to customize terminology (fig. 2) to the needs of a particular business. With this tool, termed a glossary manager (fig. 2), a company can customize a number of feature names (fig. 2) in the system to provide a more familiar context (fig. 2) for their users. A system administrator can also customize the manner in which "thumbnail" or "preview" images (fig. 2) are presented. The system performs clustering on search queries, and searches media records multi-modally, using two or more approaches such as image searching and text searching. An administrator can tune search parameters. Two or more streams of metadata may be aligned and correlated with a media file, facilitating later searching. The system evaluates itself. It folds popularity information into rankings of search results.

WO 02/19147 A1

BEST AVAILABLE COPY



CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- entirely in electronic form (except for this front page) and available upon request from the International Bureau

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Method and Apparatus for Digital Media Management, Retrieval, and Collaboration

Background

5 Creative designers in various fields work with materials from many different sources when they develop an advertisement, film, brochure, or other finished product. These materials may have been created originally by the creative designer, but for a different project, and stored in a media library or archive for later reuse. They may have been created by colleagues, and stored in an area that allows different individuals to collaborate on materials.

10 Or they may have been created by professional artists for licensing or sale. These materials are often called rich media files, or assets. Rich media files may include, but are not limited to, video, photography, graphics, audio, mixed media files, logos, presentations, and text. These media files can exist in the widest possible range of formats. It is a ponderous task to manage such assets. Annotation mechanisms for such assets include the system described in

15 U.S. Pat. No. 5,493,677, assigned to the same assignee as the assignee of the present invention. Systems to manage such assets include that described in U.S. Pat. No. 6,012,068.

It would be desirable to have a management system for digital media which streamlines the task of accounting for rights to use such media, including copyright rights. Systems relating

20 to rights management include those described in U.S. Pat. Nos. 4,337,483, 5,201,047, 5,260,999, 5,263,158, 5,319,705, 5,438,508, 5,629,980, 5,765,152, and 5,553,143.

Users in different businesses may use different terminology to refer to the various media management functions. For example, some may use the term *library*, while others use

25 *archive*. Some may use *project workspace*, while others use *share* or *collaboration tool*. In many systems, changing terminology requires tedious programming effort which risks introducing errors into the software. It would be desirable to have a management system that conveniently permits non-technical users to customize such terminology on a per-system basis. U.S. Pat. No. 5,850,561 describes a glossary construction tool for creating glossary

30 from text.

Different companies using the software according to the invention may have different corporate culture, image, and system context within the company. It would be desirable to have a management system that conveniently permits non-technical users to customize the software on a per-system basis with respect to such corporate concerns.

5

In a typical asset management system, users browse through media file collections and view thumbnail images of files to decide which files they want to work with. These thumbnails are browseables, or small representations of the actual images, videos, or other media files in the system. A browseable is created by optimizing an image or video frame for online browsing, so a browseable has lower resolution and smaller dimensions than the original file. It is commonplace, however, to find that the resolution and dimensions are not well suited to the company. It would be desirable to have a management system that conveniently permits a system administrator to customize the software in this respect.

10

15

Natural language processing (NLP) techniques are well known, including their use in information retrieval applications (Strzalkowski, 1993), (Strzalkowski, Perez Carballo and Marinescu, 1995), (Evans and Zhai, 1996). Past systems have attempted to improve upon vocabulary management techniques, for example as described in U.S. Pat. Nos. 5,251,316 and 6,125,236. Past approaches for searching multimedia include U.S. Pat. Nos. 6,243,713 and 5,794,249.

20

Clustering is well known, for example in U.S. Pat. No. 5,317,507, 5,758,257, 5,675,819, 5,778,362, and 5,875,446. See also Buckley, Chris, J. Walz, M. Mitra and C. Cardie, "Using Clustering and Super Concepts within SMART: TREC 6" (http://trec.nist.gov/pubs/trec6/t6_proceedings.html); Zamir, Oren, O. Etzioni, Madani, and Ron, KDD-97, "Fast And Intuitive Clustering Of Web Documents;" and Koller, Daphne, and Mehran Sahami, ML-97, "Hierarchically Classifying Documents Using Very Few Words." Rankings relating to relevance are discussed in U.S. Pat. No. 5,642,502.

25

30

The evaluation of information retrieval systems became an essential part of the field in the early '90s, and was strongly advanced by the TREC evaluations designed at NIST beginning

in 1993. The TREC evaluation contains different tracks, but the tracks all share the following common features:

- They are designed to provide a comparative evaluation between different systems, usually provided by different participants.
- The evaluation is done using strict test conditions that contain a set of queries, a collection of documents, and relevance judgements.
- The evaluations use evaluation scores such as precision and recall that supposedly predict real users' satisfaction from a system.

While these evaluations are indeed helpful in comparing the performance of different IR systems, they do not provide constant feedback on the performance of a live IR system. The base performance of an IR system could be at first evaluated using a standard measurement such as the one above, but as more media files are added to a system and users submit queries in an uncontrolled manner, it is hard to predict or estimate the performance of the system. In addition, if the system does not fall into the initial TREC evaluation tracks, it is necessary to develop an independent test case -- a very costly task. It is desirable to have a better self-evaluation system for such a digital asset manager.

Known annotation-related systems are discussed in U.S. Pat. No. 5,600,775, 6,006,241, and 5,938,724.

Summary of the invention

The software according to the invention incorporates a glossary management tool that makes it easy for each client to customize terminology to the needs of a particular business. With this tool, termed a glossary manager, a company can customize a number of feature names in the system to provide a more familiar context for their users. A system administrator can also customize the manner in which "thumbnail" or "preview" images are presented. The system

performs clustering on search queries, and searches media records multi-modally, using two or more approaches such as image searching and text searching. An administrator can tune search parameters. Two or more streams of metadata may be aligned and correlated with a media file, facilitating later searching. The system evaluates itself. It folds popularity information into rankings of search results.

Description of the drawing

The invention will be described with respect to a drawing in several figures, of which:

Fig. 1 shows a typical rights management editor interaction;

Fig. 2 shows a typical customization interaction screen;

Fig. 3 shows a screen permitting customers to adjust search parameters;

Fig. 4 shows a sample of a face-matching system according to the invention;

Fig. 5 illustrates a viewer according to the invention with text annotation box.

Detailed description

The inventive software manages media files, or assets, making it possible to store and retrieve them, to collaborate with colleagues to edit and work with them, and to deliver them, either for further processing or in finished form for use.

The workflow of the inventive software is designed to provide flexible choices among features that support a creative user who works with rich media files. As soon as a user logs on to the software (an optional step), she can immediately see if any system-internal messages are waiting in her system email inbox, either sent from other users collaborating with her on media files, or sent automatically by the inventive system to notify her of various occurrences

that may pertain to her work, such as a project update. The user can read her messages, reply to a message, or compose a new message to send to another system user. A composed message may consist of text only, or it may have a system-internal file attached.

5 The user may wish to work on a project, such as an advertising campaign. She enters the project work area, and creates a new project. This creates a virtual workspace in the inventive system that is dedicated to holding media files and all their related files, including edited versions, colleague comments, official approvals, and so on. She decides which users will be allowed to share access to the project space. She may upload files that she has already
10 created into the project work area. From there, she can send a media file off to a colleague for comments, editing, or approval.

If she decides to rework a previously created file for use in the new ad campaign, she can search for the file in the file storage area of the inventive system. She enters search terms,
15 generally either by typing or by speaking into an input device, and finds an appropriate media file. She then saves the file to her new project. She may decide, instead, to have the full, high-resolution version of that file sent to her for a different project. In the inventive system, delivery options for high-resolution files include on-line delivery via ftp, http, or special network; via CD delivery, or even via mail delivery of the file in analog format. Ordering and
20 file delivery in the inventive system are subject to several conditions, which the software verifies and tracks. These conditions include whether the user has the proper rights and permissions, not only to view the file but also to use or publish it. If use is subject to a fee, the fee must be paid, whether by billing, credit card, or other means. If usage requires personal approval, the request is routed to the right person and approval is granted and
25 tracked, all within the inventive software system.

Rights management. If a user determines that she needs to use a rights-restricted media file, she must engage in a dialogue with the inventive software about her planned use of the file. Companies can customize sets of questions that the software presents to users, depending on
30 which file a user wants to order. The user may have to answer whether she intends to publish the file, where it will be published, to what size audience, at what location, on what date. The

answers determine whether the file can be made available, and can also determine the price. For example, if she is showing ten seconds of a movie for a one-time training seminar in Canada for an audience of fifty people, her cost may be far less than making those same ten seconds of movie available on the home page of a major entertainment Web site. And making the entire movie available on the Web may perhaps not be permitted at any price.

When users order files in the software according to the invention, the rights management process controls every aspect of the order. A company may allow its employees to use its media files for personal use, marketing use, or in an internal organization project. Or they may allow all three uses in different situations. They can track the user's use of the files, they can designate the licensing type for the files and make sure a rights agreement is included, and they can enforce legal or company policy restrictions that may apply. The rights management process helps clients establish all of these elements so they can apply them appropriately to their stored media files.

The invention described here makes it easier for individual clients to customize a rights management setup so that the software will make the right pricing and availability decisions for each projected use. Central to the system is a question-answering paradigm: an administrator or a manager decides what questions should be presented to each potential user of a file, and what set of multiple choice answers to supply. The software maps the questions and answers to a rights and usage package, and, if applicable, each package is assigned pricing.

For example, an administrator may determine that a file's availability depends on:

What department is giving the presentation?

Who is the audience?

Will the image be included in any handouts?

Will the image be displayed on an overhead?

When is the presentation date?

Does the work contain images of any sculpture, painting, drawing, or other art object that may be copyrighted?

5

The questions, in turn, are grouped appropriately for a company's particular file collections, and are assigned to either groups of files or individual files. Questions and their answers may serve as fundamental criteria for whether a file is made available; they may serve as modifiers to an available file by raising or lowering pricing depending on usage; or they may simply be informational questions that do not play a role in decision-making, but allow companies to track file use and user needs.

10

The rights management process. When ordering files, users answer questions that ask for information about how they are planning to use the files they order. The questions a user answers are the usage questions a company designates for each possible use. This set of usage questions is called a rights package. Creating a rights package is the first step in the rights management process.

15

A rights package, or set of questions, is added to other rights packages, to make up a rights package group. This allows a company to make more than one rights package available for a group of files. A rights package group is added to a particular license type. The license type describes the possible ways a file can legally be used. A rights agreement is added to define details clearly about the user's rights. In the final step, the rights agreement is associated with a particular license type through a control table. The control table also contains pricing and approval information for each rights package.

20

25

The core piece of this process is the creation and grouping of questions that cover a company's business and legal interests for their stored media file usage. Part of this process is completed with what may be termed a rights package question role editor. A typical editor interaction is shown in Fig. 1.

30

Glossary Customization Tool and Usability Customization Tool. The software according to the invention incorporates a glossary management tool that makes it easy for each client to customize terminology to the needs of a particular business. With this tool, termed a glossary manager, a company can customize a number of feature names in the system to provide a more familiar context for their users.

The system also includes a usability management tool that customizes the software interface “look and feel” to more closely reflect a company’s corporate culture, image, and to reflect the system context within the company. A part of the system termed a usability manager allows a company to change system background colors, fonts, and the embedded logo. This tool also makes localization into a different language simpler. A typical customization interaction screen is shown in Fig. 2.

User-configurable browseable generation. In a typical asset management system, users browse through media file collections and view thumbnail images of files to decide which files they want to work with. These thumbnails are browseables, or small representations of the actual images, videos, or other media files in the system. A browseable is created by optimizing an image or video frame for online browsing, so a browseable has lower resolution and smaller dimensions than the original file. The browseable (the proxy of the actual media file) is what the user sees in the system according to the invention, and browseable size is generally set by a system administrator for use throughout the system. Importantly, the system permits generating these lower-resolution proxy files in a way that can be configured by the customer.

Natural language processing techniques. In the system according to the invention, the natural language processing component is layered. The system architecture supports a conventional search algorithm, which operates as a plug-and-play support application. The algorithm is then used in a word expansion process. The word expansion is applied to both a user’s search query, and to the stored files’ captions, that is, descriptive metadata identifying individual files.

When a user submits a search query, the query undergoes several types of NLP processing (detailed below), and the result of each element in the processing adds new query components (for example, synonyms) and/or weights (which emphasize or de-emphasize words depending on their value to the query). The resulting, or processed, query contains expanded terms and weighting information that can be passed to any search engine. This makes it possible to use multi-search agent (or "federated search") applications as well.

To expand a user search query, once a user query is received, it is divided into individual tokens, which may consist of single words or multiwords. (Multiwords are words the search engine recognizes as one unit, instead of as separate words. With this feature, when a user searches for sea lions, the system does not bring up lions by the ocean.) For this process, a variation of conventional pattern matching is used. If a single word is recognized as matching a word that is part of a stored multiword, the processor decides whether to treat the single word as part of a multiword, based on the contents of the stored pattern and the input pattern. Stored patterns include not just literal words, but also syntactic categories (such as adjective or non-verb), semantic categories (such as nationality or government entity), or exact matches. If the input matches the stored pattern information, then it is interpreted as a multiword rather than as independent words.

Processing then determines whether the resulting word is a function word (closed-class) or content word (open-class). The processor ignores function words. For content words, the related concepts for each sense of the word are retrieved from the semantic net. If the root word is unknown, the word is treated as a keyword, requiring an exact match.

The system then matches the expanded, weighted search query with stored media files in order to return search results to the user. Media files are identified by the metadata associated with them, e.g. in a caption. Text-based files can be identified by metadata associated with them, and also by their content. When users import media files into the system, the software provides a workflow to add captions to each file. The files are then uploaded into the database, and the file captions are expanded and the information stored for later file searching.

To expand the file captions, the processor looks up each word in the caption or text. Words that may be related in the semantic net are located based on stored links, and the looked-up word, along with any related words, are all displayed as the "expansion" of that word. The processor determines whether the current word or phrase corresponds to a proper name, a location, or something else. If it corresponds to a name, a name expansion process is invoked that displays the name and related names such as nicknames and other variants, based on a linked name file. If the current word or phrase corresponds to a location, a location expansion process is invoked that accesses a gazetteer and displays the location and related locations based on linked location information found in the gazetteer and supporting files. If the current word or phrase is neither a name nor a location, it is expanded using the semantic net links and weights associated with those links. Strongly related concepts are given high weights, while more remotely related concepts receive lower weights, making them less exact matches. Thus, for a query on car, documents or metadata containing car and automobile are listed highest, followed by those with sedan, coupe, and convertible, and then by more remotely related concepts such as transmission, hood, and trunk.

Once the expansion is complete, the expanded word or phrase is stored in an index database, where it is available for use in searching as described below. Processing then returns to expand the next word or phrase in the text or caption.

The system according to the invention handles certain words and phrases individually. Multiwords are matched as a whole unit, and names and locations are identified and looked up in the separate name and location files. Next, noun phrases and other syntactic units are identified. A part-of-speech tagger uses linguistic and statistical information to tag the parts of speech for sections of the user query. Only words that match by part of speech are considered to match, and if two or more parts of speech are possible for a particular word, it is tagged with both. After tagging, word affixes (i.e. suffixes) are stripped from query words to obtain a word root, using conventional inflectional morphology. If a word in a query is not known, affixes are stripped from the word one by one until a known word is found.

An intermediate query is then formulated to match against the file index database. Texts or

captions that match queries are then returned, ranked, and displayed to the user, with those that match best being displayed at the top of the list. In an exemplary system, the searching is implemented by first building a B-tree of ID lists, one for each concept in the text database.

The ID lists have an entry for each object whose text contains a reference to a given concept.

5 An entry consists of an object ID and a weight. The object ID provides a unique identifier and is a positive integer assigned when the object is indexed. The weight reflects the relevance of the concept to the object's text, and is also a positive integer.

10 To add an object to an existing index, the object ID and a weight are inserted into the ID list of every concept that is in any way relevant to the text. For searching, the ID lists of every concept in the query are retrieved and combined as specified by the query. Since ID lists contain IDs with weights in sorted order, determining existence and relevance of a match is simultaneous and fast, using only a small number of processor instructions for each concept-object pair.

15

Search Technologies. The system allows users to search for media files with many different types of search queries. For example, users may submit search queries by speaking them, typing them, copying them, or drawing them.

20 The process of locating a particular file in a large archive is a special area for innovation within the inventive software. Files are characterized in several ways. First, they have an identifier, generally similar to a filename, which is unique within the system and makes it possible to link up all the objects related to a file. These can include the actual high-resolution asset, lower-resolution thumbnails or other proxies for browsing, and
25 information about the file, or metadata. Searching can be performed on the file identifier, or it can be performed on the metadata. In the case of metadata searching, it is desirable to offer search alternatives that go beyond the exact matching process involved in a standard keyword search.

30 Some systems use controlled vocabulary searching as an optimization of keyword searching. Keyword searches simply match exactly on any word in the user's search query that appears

in the search target. (In the system according to the invention, the search target is the metadata describing a media file.) The set of potential keywords is quite large (as large as the vocabulary of English, or whatever language(s) are being used). If there are no limitations on the search vocabulary that can be employed, a user can enter a search for puma and fail to find any files captioned as mountain lion or cougar, even though they all refer to the same thing. Controlled vocabulary is an attempt to address this problem, albeit at considerable cost. In a controlled vocabulary retrieval system, cataloguers all agree to use the same terms. In practical terms, this implies that, when cataloguing, they must check their controlled vocabulary lists and be sure not to deviate. Sometimes tools can be built to aid in this process, depending on the size of the controlled vocabulary. Similarly, tools can also be provided to searchers to control their search requests. However, controlled vocabulary systems do not scale beyond a few thousand terms, since it is impractical to look up every word in English for every search. For broader retrieval systems, for faster cataloguing, and for simpler searching, a different approach is superior.

In addition to standard keyword and Boolean searching, the system software incorporates additional advanced technology for locating stored files. Rather than limiting searching to a controlled vocabulary, the system software includes natural language search, which allows cataloguers and users to employ any words in English (or whatever natural language the retrieval system is using).

Natural language search incorporates:

- a semantic network of concepts
- additional linguistic techniques, including:
 - phrase matching
 - derivational morphology, in lieu of stemming
 - part of speech tagging
 - name recognition
 - location recognition

User-Tunable Search Parameters. The system according to the invention provides a screen for customers to adjust search parameters, to reflect their company use of stored media file collections. This is shown in Fig. 3. While the parameters may themselves be well-known in a searching system, what is emphasized here is that the user (or, more likely, an administrator) can be granted access to such fundamental decisions about search as:

(a) how good a match has to be before it is displayed to the user, e.g. 50%, and

(b) how "creative" the search should be, i.e. how much should the search terms be expanded to include more distant synonyms and related terms.

It should be borne in mind that the system according to the invention can be carried out on an internet, meaning an IP-based network, and in particular may be carried out on the Internet, meaning the global IP-based network.

Multimodal Search. Currently, search methods focus on textual input. The current invention incorporates new search techniques, and combines them in novel ways.

Image search is becoming useful in commercial applications. In the system according to the invention, user search input is provided in a new way. Users may wish to select an existing image as example input, so that a search consists of "Give me more images like this."

Perhaps even more useful is the ability to select part of an image, analogous with "Give me more like this part." In the system according to the invention, identifying the part may be done in either of two exemplary ways:

1. Touch screen: user touches the screen to identify the portion of the image that feeds into the search.

2. Markup, using pen or other screen drawing metaphor, including through the system media viewer, which is described in more detail below.

In addition, search modalities can be combined. This novel approach to search is particularly applicable to multimedia. Examples of combined, or multimodal, searches, include:

- voice and text
- touch screen and text
- drawing and voice
- drawing and touch screen

and so on.

Vocabulary Management. Ideally, the semantic net of concepts is quite large and attempts to incorporate every word or term in English (or other language being used for cataloguing and searching). No matter how large the semantic net may be, there will be a periodic need to expand or edit it. New words appear in English periodically, and, although many may be slang and therefore not particularly important in a business context, some will be real new words and will be important enough to include. For example, *rollerblading* and *in-line skating* are relatively new terms in English, and depicting those actions is useful in advertising. So the terms need to be added to the semantic net. Semantic net/vocabulary maintenance is generally a manual process, particularly where the user has an existing media library with a thesaurus and vocabulary management process. Such maintenance can also be performed automatically.

To maintain a vocabulary for an information retrieval application that accepts user queries in natural language, a user maintaining a semantic net would track search queries in a query log. From the query log, he would determine which words are actually novel and are candidates to be added to the system vocabulary, by expanding the query log using morphology, and possibly a spell checker and name identifier. The remaining terms that were not matched are the basis of a list for adding terms to the vocabulary.

Tools to manage vocabulary include:

· *A morphological analyzer.* This tool strips off any endings and morphological alterations in a query to find the stem, and checks to see if the stem is in the current vocabulary. If the stem is not, the user doing the maintenance might try:

5 · *A spell checker.* This tool uses the conventional algorithms to see if the supposedly new word is actually a misspelling of a known word. If it is not a misspelling, the user might try:

10 · *A name identifier.* This tool checks to see if the supposedly new word is in a name configuration, in that it follows a known first name in the query. If it does, it is added to a candidate name database. If it is not, it is proposed as a possible new word to be added to the system's vocabulary.

15 *Searching Audio/Video by Timecode Correlation with Search Criteria.* Video and audio files can be timecoded, or marked such that the software in which they run can locate a specific frame (for videos) or measure (for audio) at any time. Importantly, the system according to the invention permits searching time-based media, including video and audio files, by combining two search elements. The first is a standard search, including but not limited to natural language search. The second is a time indicator, such as a SMPTE (Society of Motion
20 Picture and Television Engineers) standard timecode. Face recognition is an additional technology that can be used in searching. Face recognition is a subset of the more general technology of object recognition, and indeed techniques described here may extend to additional technologies as well.

The current state of the art in face recognition technology makes it possible to take a
25 manually created, labeled library of faces, and match faces from a video to that library. For example, a user might work with a news video and use a face recognition program to label Nelson Mandela in it. The output of the face recognition program would be a time-coded segment, with start and stop times, of when Nelson Mandela was on camera, with the label "Nelson Mandela" attached to the time codes. While face recognition currently does not
30 achieve 100% precision or recall, it can still be useful. For example, one known system offers a contract rights management capability for films that demands time-coded segments

with names attached, and assumes that users will create those manually, so that the correct contract restrictions for each film segment can be attached to the right time codes. Given a small library of the actors in a film, it would be possible to do a fast, automated match-up of time codes and actors, even with imperfect face recognition technology. Selecting the correct actor from forty publicity shots would be much simpler than selecting from among thousands of faces.

Importantly, the system according to the invention carries out the automated creation of the face library. Required elements include time-coded metadata (for example, the voice recognition transcript of a video), and the ability to find the names of people in text. Each time a face and a person's name appear at the same time code, that occurrence is a potential new entry for the face library. A user may run the face-to-name matcher for thousands of hours and sift out the recurring matches as the most likely. In this way, a reference library of faces is created, and new material can be catalogued automatically.

The software according to the invention approaches this by using alignment techniques to match up two or more streams of metadata. For example, a broadcast news program may contain closed captioning for the hearing-impaired. It may also contain a separate description of the news footage, probably created manually by the news department. The system according to the invention uses alignment to match the description, which is not time-coded, with the closed captioning, which is time-coded. This process allows the system to add time codes to the non-time-coded stream. The software then uses that new, derived stream (i.e. the description with newly added time codes), and searches for proper names within it. At the same time, using face recognition algorithms on the video stream, the software finds faces. The system tries to match up the faces with the proper names that describe who they are. This matched set provides us with a rough cut of a face (or object) reference library. This is exemplified in Fig. 4.

Face recognition can also be employed to manage the library or archive of media files. Media libraries are assembled over time, often from disparate sources, and may contain multiple copies of a single media file, either with the same metadata or with different metadata.

Duplicate detection is therefore an important element of library and archive management, and face recognition (and, more generally, image recognition) can be leveraged to provide that capability. More broadly, for video, scene detection technology can assist in the process of identifying duplicates so that they can be purged from the library.

5

Clustering and Other Ways to Determine Stored File Usage. Clustering involves combining user search queries in such a way that the searches can be analyzed usefully to provide answers to business questions. Clustering has received considerable attention in document information retrieval (IR) and more recently, in video IR as a means of refining retrieval results based on user preferences or profiles, and to characterize the marketplace. The prior art contains many examples of clustering applied in information retrieval systems, but they all apply to search results returned to users rather than search queries submitted by users. In the system according to the invention, we cluster search queries by topic. We then use that information to adjust the collections of stored files so that the file collections will better meet users' needs.

10

15

This system characterizes the information needs of groups (and subgroups) of users, with respect to a collection of media files (e.g. images, videos, sound clips, text, multimedia objects). Some common groupings include:

20

- search queries that brought back no files
- search queries that brought back no files the user was interested in
- search queries that lead to expressions of user interest or sales

25

This system applies clustering technology to user-submitted search queries, and to the files retrieved in search results. It also includes:

30

- machine learning as applied to the above.

- characterizing the information needs over time, by user type, or by other factors.
- methods for reporting file collection needs to interested parties (for example, media suppliers). The system informs a supplier that pictures of earthquakes are selling briskly, or that users keep looking for videos of dance performances but cannot find any.
- methods for adjusting file collections based on the results of the clustering analysis, above.
- novel clustering techniques. These include using a semantic expansion (such as the WordNet hierarchical thesaurus) and phrase identification (such as noun phrase, and name and location identification) as the basis for the clustering.

Before user queries can be analyzed, they must be expanded to a “common denominator”. To expand the user search queries, we use natural language techniques. Specifically, we treat each query as if it were metadata within our system, as described in the NLP section, above. Each query is expanded through the application of a semantic net, so that it contains synonyms and related terms. This expansion provides a set of features to which we can apply standard clustering technology.

Obtaining valuable information on user preferences for stored files begins with deciding what information a client wants to understand. The data set can be selected according to various criteria, including:

- queries from a particular subset of users (e.g. registered users, users by industry, new users)
- queries that lead to success (sale or other indication)
- queries that lead to failure

A first step is to select the data set on which clustering is to be performed. In an information retrieval (IR) context, clustering can be performed on queries or on assets to be retrieved (documents, images, video, audio, mixed media). A sample query set may include short queries, as is standard on Web searches, long queries, as seen in TREC (U.S.

5 government-sponsored text retrieval conferences), or as produced by QBE (query by example), in which an asset or set of assets are themselves inserted into a query.

A second step is to perform analysis on the queries using, for example, linguistic methods, such as:

10 • Tokenization: determine word/token boundaries. In English, tokenization mostly coincides with spaces between words, with certain complications (Alzheimer's = 1 token vs. she's = 2 tokens).

15 • Morphology or stemming: removed tense and plural markers and other affixes to find the word root.

20 • Identify names, locations, noun phrases: using a pattern matcher or other methodology, determine words were groupings for special handling. For example, for names, match certain kind of variance; for locations, match subset; for noun phrases, we to complete and head-only matches higher than modifier home-only matches.

A third step is to expand the queries. Ideally, this step includes expansion using a thesaurus or semantic net of synonyms, super-terms, and other relationships.

25 A fourth step is, for each of the terms in each expanded query, assign a weight based on how close that term is to the original query. The exact weighting will vary by application, but the basic understanding is that more closely matching terms are weighted close to 100.

30 A fifth step is to create a vector for each expanded query. In order to apply a statistical clustering algorithm, we arrange the vectors into a matrix.

A sixth step is to apply a statistical clustering algorithm in order to group similar queries together. A hierarchical or linear clustering strategy may be used, depending on whether the desired clusters are hierarchical or not. Clustering may allow overlap, which means that a query may appear in more than one cluster.

A seventh step is to apply the clustering algorithm until the stopping condition is met, e.g. the desired number of clusters is obtained, or a combination of cluster number and desired distinctiveness of clusters is reached.

An eighth step relates to the clusters. Clusters are most useful to a human observer if they bear useful names that reflect the content. Use a semantic net hierarchy, combined with term frequency in a reference corpus, to identify the lowest-level term in the hierarchy that subsumes all the queries.

Folding Popularity Into Rankings. Many information retrieval applications currently incorporate relevance feedback into their judgements of how to rank search results returned to a user. In all cases, however, the past systems utilize explicit user feedback, not implicit feedback. That is, they rank files by requiring a user to indicate what items he is interested in, once a set of items is returned by a search. Importantly, in the system according to the invention, the system discerns implicit popularity rankings based on a ranked set of user actions. The system then uses those rankings to re-rank subsequent search results. The user actions from which popularity may be determined include, but are not limited to:

- whether a file is placed in a projects folder or other work space

- whether a file is placed in a shopping cart

- whether a file is purchased

In addition, implicit popularity rankings may be derived from one user or set of users and applied to a different user or set of users. For example, if User A places a media file in a

projects folder or shopping cart; the information on her activity can also be used to re-rank search results for User B, who is in some way similar to user A. In another example, if users with ".edu" e-mail addresses buy certain things, it makes sense to re-rank search results to favor those things when showing results to other ".edu" users. In the system according to the invention, if registered users who work for advertising agencies have placed certain items in their shopping carts, other advertising agency employees can have their search results re-ranked to favor those items. The opposite can be true as well: the same system can be used to disfavor certain items because they have been sold too many times to advertising agencies, for example.

Retrieval system self-evaluation. The retrieval system according to the invention does not answer any of the TREC tracks — a media file is described by a short paragraph or by keywords. Even though it is possible to develop a unique test collection for purposes of evaluation, it will not necessarily predict the performance of new systems, or even for existing ones.

What is now described is a method for ongoing evaluation of IR system performance based on search results combined with user feedback. This approach enables the system to alert a human system manager about observed degradation in the system performance. As the performance evaluation system becomes more knowledgeable through methods of machine learning, the system is desirably able to change its own parameters in order to improve its performance.

"Performance" as used in this inventive system is a score on a scale of user satisfaction with the respect to search results rankings. User satisfaction is determined by tracking the user actions together with the system's data. For example, for a very good performance, the user would submit a search query and purchase the media file that was ranked first. Possible indications of poor performance might include a user issuing several consecutive queries, getting thousands of results, and terminating the session without further examining any of the media files.

Viewer. The software application according to the invention includes a viewer for annotations, or mark-ups, of full motion digital still images, video frames, or other indexed data structures. The viewer, preferably accessible on a personal computer with a Web browser, serves as a helper application for the underlying application of the system according to the invention. The viewer allows users to view and mark up (comment on) media on a separate, see-through, lightweight layer. The viewer supports annotations that are created and rendered so that they appear overlaid on the related media. Position, size, frame number, and other attributes of annotations are saved in a separate annotation file, and when played back the annotations appear at the saved location and with the saved attributes. Preferably, to the greatest extent possible, creating and editing of annotations is be done in WYSIWYG (what you see is what you get) fashion. This is illustrated in Fig. 5.

The annotations may consist of text, graphics, and digitized audio, and are stored separately from the original file information. An indexing scheme relates individual annotations to individual video frames. On full motion video playback, the annotations are displayed on the originally annotated frames. One central part of the system according to the invention is the use of a downloadable, view-only application, which enables users who do not have the full power to create annotations nonetheless to be able to view annotations created by others.

In an exemplary embodiment, files are stored centrally. Preferably the viewer provides security, e.g. SSL, server authentication, and proxy authentication. The underlying application according to the invention powers the full lifecycle of digital media from content collaboration, deep storage, search and retrieval using a natural language search and the ability effectively to move bandwidth-intensive media over the Web. The software is preferably Web-based.

The viewer is a standalone, platform-native "helper" application that is normally launched by a Web browser, from a specific link on a Web page that is part of the Web server of the system according to the invention. The viewer has the ability to upload annotation data back to the Web server. Except for the two actions of launching and uploading, the viewer does not require any network connection with the Web server or the Web browser.

The current viewer in the system according to the invention on a PC or Macintosh platform allows the user to view and annotate various video, still image, audio, and text formats, including MPEG, QuickTime, or RealMedia videos, bitmap, jpeg, and tiff images, MP3, .wav, .aiff, .au, and .snd audio files, and .pdf document files. The viewer currently has nine
5 modes in which it can operate, all of which would be relevant to the mobile user. They are:

- annotate a media file
- select a keyframe
- select storyboard frames (and optionally a keyframe)
- 10 · set the download (cache) directory
- send a message and, optionally, attached files to another user
- download a media file
- upload media files to a project
- upload media files to a public collection
- 15 · select a playlist

The current (Mac and Windows) viewers can be launched in any of these nine modes, generally by receiving an XML annotation file.

20 Attributes common to all annotation types are: position, size, frame number (video only), and page number (multipage document only). All of the graphical attributes such as colors and fonts are modifiable using platform-native dialog boxes. These attributes can be set for new annotations as well as previously created ones.

25 For video, each annotation is recorded with the timecode of the specific frame on which it was created. When movies with annotations are played back, the viewer stops playback at each frame where an annotation exists. The viewer also contains a drop-down list of all annotated frames (by timecode) so that individual annotated frames can be viewed quickly. Controls are also provided for stepping by a single frame in either direction, as well as a
30 control displaying the timecode of the current frame where the viewer is paused.

The PDA (or handheld or wearable) version of the viewer builds on the same general architecture. The server generates a simple XML annotations file, sends it to the client (i.e. the viewer via the Web browser), and handles the returned HTTP messages from the viewer. The following annotation types are desirably supported on a PDA version:

5

Type	Attributes
Freehand drawing (pen)	Line widthColor
Transparent text	Font name, Font size, Font color
Sticky note	Font name, Font size, Font color, Background color
10 Sound	Audio data

15

In this way, the system according to the invention supports the full life cycle of media, allowing organizations to expedite the process of searching, collaborating and distributing of digital assets, such as imagery, video files, pictures and text documents. Users desirably have the freedom to collaborate anywhere at anytime using the annotation viewer according to the invention on a PDA. Users are preferably able to annotate video and still images with a virtual pen, sticky note, text and even voice using a wireless modem. Annotations are preferably capable of being added, edited, moved, or deleted.

20

A PDA-based digital media management solution takes digital delivery and collaboration to the next level by eliminating the need of a traditional PC and Ethernet connection. In addition, users no longer need to carry laptops to stay up to date on work involving video or still images.

25

Preferably the viewer supports both HTTP authentication and Proxy authentication. As an option, the viewer displays a login dialog where the user can enter a user ID and password to be used for authentication. Since the viewer is activated and closed frequently, it should not prompt the user to log in each time it connects to the server. The viewer instead provides a mechanism for saving the user ID and password on the local workstation (in encrypted form) and passing this information to the server without any prompting. It is desirable that the viewer support SSL encryption for all of its HTTP requests.

30

This Page Blank (uspto)

We claim:

1. A method for use with first and second metadata streams with respect to a video stream, the first metadata stream time-coded with respect to the video stream and the second metadata stream not time-coded with respect to the video stream, the method comprising the steps of:

aligning the second metadata stream with the first metadata stream;

adding time codes to the second metadata stream, based on the alignment;

searching for proper names within the second metadata stream;

finding faces within the video stream;

matching faces with proper names; and

placing the matched faces and proper names into a reference library.

2. The method of claim 1 wherein the video stream is news footage, wherein the first metadata stream is closed captioning for the hearing impaired, and wherein the second metadata stream is a separate description of the news footage.

3. A method for use with a system storing myriad digital media files, the method comprising the steps of:

generating myriad first thumbnail images, each first thumbnail image corresponding to one of the digital media files, each first thumbnail image having lower resolution and smaller dimensions than the corresponding digital media file, each first thumbnail image having first dimensions;

displaying a subset of the first thumbnail images, the subset comprising more than one and

less than all of the myriad first thumbnail images, the subset created as a result of input from a first user;

receiving a configuration command from a second user, the configuration command
5 indicative of second dimensions differing from the first dimensions;

generating myriad second thumbnail images, each second thumbnail image corresponding to one of the digital media files, each second thumbnail image having lower resolution and smaller dimensions than the corresponding digital media file, each second thumbnail image
10 having second dimensions;

displaying a subset of the second thumbnail images, the subset comprising more than one and less than all of the myriad second thumbnail images, the subset created as a result of input from a third user.

15 4. The method of claim 3 wherein the first and third users are the same user.

5. The method of claim 3 wherein the first and third users are different users.

20 6. A method for use with a system storing myriad digital media files, the method comprising the steps of:

generating myriad first thumbnail images, each first thumbnail image corresponding to one of the digital media files, each first thumbnail image having lower resolution and smaller
25 dimensions than the corresponding digital media file, each first thumbnail image having first dimensions;

displaying a subset of the first thumbnail images, the subset comprising more than one and less than all of the myriad first thumbnail images, the subset created as a result of input from
30 a first user;

receiving a configuration command from a second user, the configuration command indicative of second resolution differing from the first resolution;

5 generating myriad second thumbnail images, each second thumbnail image corresponding to one of the digital media files, each second thumbnail image having lower resolution and smaller dimensions than the corresponding digital media file, each second thumbnail image having second resolution;

10 displaying a subset of the second thumbnail images, the subset comprising more than one and less than all of the myriad second thumbnail images, the subset created as a result of input from a third user.

7. The method of claim 6 wherein the first and third users are the same user.

15 8. The method of claim 6 wherein the first and third users are different users.

9. A method for use with a system storing digital media records, the system comprising a vocabulary file of words keyed to the digital media records, the method comprising the steps of:

20 receiving a search query by computer from a user, the search query including words;

logging the search query by computer, yielding a query log;

25 processing the query log to identify words in the query log which are not words already included in the vocabulary file and which are not words which are variants of words already included in the vocabulary file, the processing performed by computer, said words defined as "not-found words;"

30 adding the not-found words to the vocabulary file, and

keying the not-found words to the digital media records.

10. The method of claim 9 wherein the vocabulary file further comprises a thesaurus and the step of keying the not-found words to the digital media records comprises adding the not-found words to the thesaurus.

11. The method of claim 9 wherein the adding and keying steps are performed manually.

12. The method of claim 9 wherein the adding and keying steps are performed automatically.

13. The method of claim 9 wherein the processing step comprises morphological analysis.

14. The method of claim 9 wherein the processing step comprises spell checking.

15. The method of claim 9 wherein the processing step comprises name identification.

16. A method for use with a system storing digital media records, the system comprising a data file defining rights management questions and multiple-choice answers thereto, the method comprising the steps of:

receiving, from a first user, a selection of rights management questions and respective multiple-choice answers for the data file;

receiving, from a second user non-identical to the first user, a query regarding a first digital media record;

presenting, to the second user, a first rights management question among the selection of rights management questions;

receiving, from the second user, a multiple-choice answer from among the respective multiple-choice answers with respect to the first rights management question, and storing

same;

presenting, to the second user, a second rights management question among the selection of rights management questions;

5

receiving, from the second user, a multiple-choice answer from among the respective multiple-choice answers with respect to the second rights management question, and storing same;

10

presenting, to the second user, a third rights management question among the selection of rights management questions;

receiving, from the second user, a multiple-choice answer from among the respective multiple-choice answers with respect to the third rights management question, and storing same;

15

deriving pricing information for the second user with respect to the first digital media record from the stored multiple-choice answers;

20

receiving, from a third user non-identical to the first user and non-identical to the second user, a query regarding a second digital media record;

presenting, to the third user, a fourth rights management question among the selection of rights management questions;

25

receiving, from the third user, a multiple-choice answer from among the respective multiple-choice answers with respect to the fourth rights management question, and storing same;

presenting, to the third user, a fifth rights management question among the selection of rights management questions;

30

receiving, from the third user, a multiple-choice answer from among the respective multiple-choice answers with respect to the fifth rights management question, and storing same;

presenting, to the third user, a sixth rights management question among the selection of rights management questions;

receiving, from the third user, a multiple-choice answer from among the respective multiple-choice answers with respect to the sixth rights management question, and storing same;

deriving pricing information for the third user with respect to the second digital media record from the stored multiple-choice answers.

17. The method of claim 16 wherein:

the first and fourth rights management questions are the same;

the second and fifth rights management questions are the same; and

the third and sixth rights management questions are the same.

18. A method for use with a system storing digital media records, the system comprising a search engine the operation of which is defined by a plurality of stored parameters, the stored parameters defining, for the search engine, an extent to which the search engine expands search terms, the system communicatively coupled to an internet and providing a hypertext transfer protocol server interface to the internet, the method comprising the steps of:

receiving from a first user, via a hypertext transfer protocol client session, a change to one of the parameters;

storing the change to the one of the stored parameters;

receiving from a second user, via a hypertext transfer protocol client session, a search request;
passing the search request to the search engine;

5 performing, by the search engine, a search determined by the search request and determined by the stored parameters; and deriving search results therefrom;

reporting the search results to the second user.

10 19. A method for use with a system storing digital media records, the system comprising a search engine searching said digital media records, the method comprising the steps of:

displaying all or part of a first digital media record to a user;

15 receiving, from the user, first information indicative of a selection of less than all of the displayed portion of the first digital media record;

receiving, from the user, second information indicative of text;

20 performing, by the search engine, a search of the digital media records with respect to the first information and the second information, and deriving search results therefrom; and

displaying the search results to the user.

25 20. The method of claim 19 wherein the step of receiving first information comprises the user touching a screen to identify the portion of an image displayed on the screen.

21. The method of claim 19 wherein the step of receiving first information comprises the user drawing on a pad to identify the portion of an image displayed on the screen.

30

22. The method of claim 19 wherein the step of receiving second information comprises the

user typing at a keyboard.

23. The method of claim 19 wherein the step of receiving second information comprises receiving voice information and performing speech recognition upon the voice information.

5

24. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

receiving search requests from users;

10

logging the search requests;

expanding the search requests;

15

applying a statistical clustering algorithm, thereby grouping similar search requests together;

identifying, using a semantic net hierarchy, a lowest-level term in the hierarchy that subsumes all of the queries in a grouping of search requests;

20

communicating the identified term to a user.

25. The method of claim 24 wherein the expanding is performed using a thesaurus.

26. The method of claim 24 wherein the expanding is performed using a semantic net comprising synonyms and super-terms.

25

27. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

30

receiving search requests from users;

performing, by the search engine, searches based upon the search requests, yielding respective search results, each search result defining selected digital media records, the digital media records each having associated metadata;

5 logging the search results and the metadata associated with digital media records selected therein;

expanding the metadata, defining expanded query metadata results;

10 applying a statistical clustering algorithm, thereby grouping similar expanded query metadata results together;

identifying, using a semantic net hierarchy, a lowest-level term in the hierarchy that subsumes all of the expanded query metadata results in the grouping of expanded query metadata results;

15 communicating the identified term to a user.

20 28. The method of claim 27 wherein the expanding is performed using a thesaurus.

29. The method of claim 27 wherein the expanding is performed using a semantic net comprising synonyms and super-terms.

25 30. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

receiving first search requests from a plurality of first users;

30 performing, by the search engine, searches based upon the first search requests, yielding respective first search results, each first search result defining first selected digital media records;

logging the first search results;

receiving, from the first users, information indicative of subsequent actions by the first users
selecting particular ones of the selected digital media records;

5

receiving a second search request from a second user;

performing, by the search engine, a search based upon the second search request, yielding
respective second search results, the second search results defining second selected digital
media records;

10

ranking the second selected digital media records downward for at least one second selected
digital media record that was selected by at least one first user.

15

31. A method for use with a system storing digital media records and comprising a search
engine searching said stored digital media records, the method comprising the steps of:

receiving first search requests from a plurality of first users;

20

performing, by the search engine, searches based upon the first search requests, yielding
respective first search results, each first search result defining first selected digital media
records;

logging the first search results;

25

receiving, from the first users, information indicative of subsequent actions by the first users
selecting particular ones of the selected digital media records;

receiving a second search request from a second user;

30

performing, by the search engine, a search based upon the second search request, yielding

respective second search results, the second search results defining second selected digital media records;

5 ranking the second selected digital media records downward for at least one second selected digital media record that was selected by at least a predetermined number of first users.

32. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

10 receiving first search requests from a plurality of first users;

performing, by the search engine, searches based upon the first search requests, yielding respective first search results, each first search result defining first selected digital media records;

15 logging the first search results;

receiving, from the first users, information indicative of subsequent actions by the first users selecting particular ones of the selected digital media records;

20 receiving a second search request from a second user;

performing, by the search engine, a search based upon the second search request, yielding respective second search results, the second search results defining second selected digital media records;

25 ranking the second selected digital media records downward for at least one second selected digital media record that was selected at least a predetermined number of times by first users.

30 33. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

receiving first search requests from a plurality of first users;

performing, by the search engine, searches based upon the first search requests, yielding
respective first search results, each first search result defining first selected digital media
records;

displaying said first selected digital media records presented in an order, said order defining a
first-presented first selected digital media record;

logging the event of a first user purchasing said first-presented first selected digital media
record;

reporting, to a second user, the frequency of occurrence of the logged events.

34. A method for use with a system storing digital media records for purchase and
comprising a search engine searching said stored digital media records, the method
comprising the steps of:

receiving first search requests from a plurality of first users;

performing, by the search engine, searches based upon the first search requests, yielding
respective first search results, each first search result defining first selected digital media
records;

displaying said first selected digital media records presented in an order, said order defining a
first-presented first selected digital media record;

logging the event of a first user issuing several consecutive search requests, and receiving
respective first selected digital media requests greater in number than a predetermined

threshold for said several consecutive search requests;

reporting, to a second user, the frequency of occurrence of the logged events.

35. The method of claim 34 wherein the logged events further comprise the first user failing purchase any of the stored digital media records.

36. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

receiving search requests from users;

performing, by the search engine, searches based upon the search requests, yielding respective search results, each search result defining selected digital media records or being empty;

logging the search requests for which the search result is empty;

expanding the logged search requests;

applying a statistical clustering algorithm to the logged search requests, thereby grouping similar search requests together;

communicating a group of search requests to a user.

37. The method of claim 36 wherein the expanding is performed using a thesaurus.

38. The method of claim 36 wherein the expanding is performed using a semantic net comprising synonyms and super-terms.

39. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the system permitting user expressions of interest in particular stored digital media records, the method comprising the steps of:

receiving search requests from users;

performing, by the search engine, searches based upon the search requests, yielding respective search results, each search result defining selected digital media records;

5

logging the search requests for which a user has expressed interest in a selected digital media record;

expanding the logged search requests;

10

applying a statistical clustering algorithm to the logged search requests, thereby grouping similar search requests together;

communicating a group of search requests to a user.

15

40. The method of claim 39 wherein the expanding is performed using a thesaurus.

41. The method of claim 39 wherein the expanding is performed using a semantic net comprising synonyms and super-terms.

20

42. The method of claim 39 wherein a user expressing interest in a selected digital media record comprises the user placing the selected digital media record into an online shopping cart.

25

43. The method of claim 39 wherein a user expressing interest in a selected digital media record comprises the user purchasing rights to use the selected digital media record.

44. The method of claim 39 wherein a user expressing interest in a selected digital media record comprises the user placing the selected digital media record into an online projects folder or other work space.

30

45. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

receiving first search requests from a plurality of first users;

performing, by the search engine, searches based upon the first search requests, yielding respective first search results, each first search result defining first selected digital media records;

logging the first search results;

receiving, from the first users, information indicative of subsequent actions by the first users expressing interest in particular ones of the selected digital media records;

receiving a second search request from a second user;

performing, by the search engine, a search based upon the second search request, yielding respective second search results, the second search results defining second selected digital media records;

ranking the second selected digital media records upward for at least one second selected digital media record that was for which at least one first user expressed interest.

46. The method of claim 45 wherein a user expressing interest in a selected digital media record comprises the user placing the selected digital media record into an online shopping cart.

47. The method of claim 45 wherein a user expressing interest in a selected digital media record comprises the user purchasing rights to use the selected digital media record.

48. The method of claim 45 wherein a user expressing interest in a selected digital media

record comprises the user placing the selected digital media record into an online projects folder or other work space.

5 49. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

receiving first search requests from a plurality of first users;

10 performing, by the search engine, searches based upon the first search requests, yielding respective first search results, each first search result defining first selected digital media records;

logging the first search results;

15 receiving, from the first users, information indicative of subsequent actions by the first users expressing interest in particular ones of the selected digital media records;

receiving a second search request from a second user;

20 performing, by the search engine, a search based upon the second search request, yielding respective second search results, the second search results defining second selected digital media records;

25 ranking the second selected digital media records upward for at least one second selected digital media record that was for which at least a predetermined number of first users expressed interest.

30 50. The method of claim 49 wherein a user expressing interest in a selected digital media record comprises the user placing the selected digital media record into an online shopping cart.

51. The method of claim 49 wherein a user expressing interest in a selected digital media record comprises the user purchasing rights to use the selected digital media record.

5 52. The method of claim 49 wherein a user expressing interest in a selected digital media record comprises the user placing the selected digital media record into an online projects folder or other work space.

53. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

10 receiving first search requests from a plurality of first users;

performing, by the search engine, searches based upon the first search requests, yielding respective first search results, each first search result defining first selected digital media records;

15 logging the first search results;

20 receiving, from the first users, information indicative of subsequent actions by the first users expressing interest in particular ones of the selected digital media records;

receiving a second search request from a second user;

25 performing, by the search engine, a search based upon the second search request, yielding respective second search results, the second search results defining second selected digital media records;

30 ranking the second selected digital media records upward for at least one second selected digital media record for which first users expressed interest at least a predetermined number of times.

54. The method of claim 53 wherein a user expressing interest in a selected digital media record comprises the user placing the selected digital media record into an online shopping cart.

5 55. The method of claim 53 wherein a user expressing interest in a selected digital media record comprises the user purchasing rights to use the selected digital media record.

56. The method of claim 53 wherein a user expressing interest in a selected digital media record comprises the user placing the selected digital media record into an online projects
10 folder or other work space.

57. A method for use with a system storing digital media records and comprising a search engine searching said stored digital media records, the method comprising the steps of:

15 receiving first search requests from a plurality of first users;

performing, by the search engine, searches based upon the first search requests, yielding respective first search results, each first search result defining first selected digital media records;

20 logging the first search results;

receiving, from the first users, information indicative of subsequent actions by the first users expressing interest in particular ones of the selected digital media records;

25 receiving a second search request from a second user;

performing, by the search engine, a search based upon the second search request, yielding respective second search results, the second search results defining second selected digital
30 media records;

ranking the second selected digital media records upward for at least one second selected digital media record for which expression of interest satisfies a predetermined threshold, wherein expression of interest comprises a weighted function of two or more of the following events: the user placing the selected digital media record into an online shopping cart, the user purchasing rights to use the selected digital media record, and the user placing the selected digital media record into an online projects folder or other work space.

58. A method for use with a metadata stream with respect to a video stream, the metadata stream time-coded with respect to the video stream, the method comprising the steps, performed by a computer, of:

searching for proper names within the metadata stream;

finding faces within the video stream;

matching faces with proper names; and

placing the matched faces and proper names into a reference library.

59. The method of claim 58 wherein the video stream is news footage, wherein the metadata stream is closed captioning for the hearing impaired.

60. A method for use with a metadata stream with respect to at least one video stream, the metadata stream time-coded with respect to the at least one video stream, the method comprising the steps, performed by a computer, of:

searching for proper names within the metadata stream;

finding faces within the at least one video stream;

matching faces with proper names;

placing the matched faces and proper names into a reference library; and

for a selected proper name, generating a list of locations within the at least one video stream associated with that selected proper name.

5

61. The method of claim 60 wherein the video stream is news footage, wherein the metadata stream is closed captioning for the hearing impaired.

10

62. The method of claim 60 further comprising the step of communicating the list of locations to a rights management system.

63. A method for use with a system for managing digital media files, the method comprising the steps of:

15

using face recognition to recognize faces portrayed in the digital media files, yielding metadata with respect to the digital media files indicative of the recognized faces;

analyzing the metadata indicative of the recognized faces to detect duplicate files among the digital media files; and

20

displaying the duplicate files for a user.

64. A method for use with a system for managing digital media files, the method comprising the steps of:

25

using image recognition to recognize images portrayed in the digital media files, yielding metadata with respect to the digital media files indicative of the recognized images;

analyzing the metadata indicative of the recognized images to detect duplicate files among the digital media files; and

30

displaying the duplicate files for a user.

65. A method for use with a system for managing digital media files, the method comprising the steps of:

5

using scene detection to detect scenes portrayed in the digital media files, yielding metadata with respect to the digital media files indicative of the detected scenes;

10

analyzing the metadata indicative of the detecting scenes to detect duplicate files among the digital media files; and

displaying the duplicate files for a user.

Questions Associated with RUP 129



Question Id	Question	Distributes Over	Role
106	new question2	Groups 	Modifier 

Figure 1

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)

Adjust the Search Engine

Update filters:

Search filters:

Sense Weight Function:

Early Stress Function:

Multiword Function:

Default minimum score:

Exact-match scale:

Root word scale:

Noun phrase scale:

Head noun scale:

Modifier scale:

Minimum tag weight:

Minimum static tag weight:

Minimum storage weight:

Gerund Verb Weight:

Gerund Noun Weight:

Minimum Tag Weight for Patterns:

Location expansion weight:

Stop Words:

Stop Tags:

Part of Speech	Search Function	Update Function
Antonym	<input type="text"/>	<input type="text"/>
Hyponym	<input type="text"/>	<input type="text"/>
Hyponym	<input type="text"/>	<input type="text"/>
Member Meronym	<input type="text"/>	<input type="text"/>
Substance Meronym	<input type="text"/>	<input type="text"/>
Part Meronym	<input type="text"/>	<input type="text"/>
Member Holonym	<input type="text"/>	<input type="text"/>
Substance Holonym	<input type="text"/>	<input type="text"/>
Part Holonym	<input type="text"/>	<input type="text"/>
Attribute	<input type="text"/>	<input type="text"/>
Enactment	<input type="text"/>	<input type="text"/>
Cause	<input type="text"/>	<input type="text"/>
Also See	<input type="text"/>	<input type="text"/>
Verb Group	<input type="text"/>	<input type="text"/>
Similar To	<input type="text"/>	<input type="text"/>
Participle	<input type="text"/>	<input type="text"/>
Pertaining	<input type="text"/>	<input type="text"/>

Sample Phrase:

Scan for ID:

Figure 3

THIS PAGE BLANK (USPTO)



Timecode	Closed Caption	Description	Face Library Candidate
0:001:002-007	former <u>president</u> Clinton	ex-president Bill Clinton	 Bill Clinton
0:003:001-008	George W. Bush's <u>Secretary of State</u> Colin Powell	Colin Powell, <u>Secretary of State</u> for George W. Bush	 Colin Powell George W. Bush

Figure 4




Figure 5

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US01/26841

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : G06F 17/00

US CL : 707/104.1

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 707/104.1, 3, 6

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EAST, WEST, US-PGPUB, IBM TDB, DERWENT

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,903,892 A (HOFFERT et al) 11 May 1999 (11.05.1999), abstract, column 3, lines 1-39, column 4, lines 1-31 and lines 56-58, column 5, lines 24-52, column 6, lines 22-46, column 7, lines 26-51, column 17, lines 7-18, column 18, lines 48-58, column 23, lines 46-67, column 24, lines 1-27, column 25, lines 14-37	19-45, 47, 49, 51, 53, 55, 57
---		-----
A		1-2, 18, 46, 48, 50, 52, 54, 56, 58-62
Y	US 6,072,904 A (DESAI et al) 6 June 2000 (06.06.2000), abstract, column 2, lines 22-38, column 4, lines 34-60, column 5, lines 56-63	24, 27, 36, 39
Y	US 5,963,205 A (SOTOMAYOR) 5 October 1999 (05.10.1999), abstract, column 1, lines 28-38, column 2, lines 42-61, column 5, lines 1-6, column 11, lines 45-55, column 15, lines 41-55	9-15
Y	US 5,251,316 A (ANICK et al) 5 October 1993 (05.10.1993), abstract, fig. 2, fig. 4, column 2, lines 37-57, column 6, lines 4-33	9-15
Y	US 5,765,152 A (ERICKSON) 9 June 1998 (09.06.1998), abstract, fig. 5, fig. 7, column 2, lines 33-58, column 8, lines 8-45	16-17
Y	US 5,822,432 A (MOSKOWITZ et al) 13 October 1998 (13.08.1998), abstract, column 2, lines 32-67, column 3, lines 1-3, column 9, lines 1-16	16-17



Further documents are listed in the continuation of Box C.



See patent family annex.

Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

04 November 2001 (04.11.2001)

Date of mailing of the international search report

13 DEC 2001

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703)305-3230

Authorized officer

Joon H Hwang

Telephone No. 703-305-6469

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US01/26841

C. (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,983,237 A (JAIN et al) 09 November 1999 (09.11.1999), fig. 2, fig. 4, column 2, lines 57-67, column 3, lines 1-12, column 4, lines 64-67, column 5, lines 1-6, column 11, lines 32-43	3-8, 63-65
A	US 5,752,244 A (ROSE et al) 12 May 1998 (12.05.1998), abstract, fig. 16, column 2, lines 11-17, column 21, lines 32-48	3-8, 63-65
A,P	US 6,243,713 B1 (NELSON et al) 05 June 2001 (05.06.2001), abstract, fig. 11, column 2, lines 4-11, column 7, lines 11-23, column 17, lines 13-24	24-29, 36-44

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US01/26841

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claim Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claim Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claim Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:
Please See Continuation Sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

☐
☐

The additional search fees were accompanied by the applicant's protest.

No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.:

PCT/US01/26841

BOX II. OBSERVATIONS WHERE UNITY OF INVENTION IS LACKING

This application contains the following inventions or groups of inventions which are not so linked as to form a single general inventive concept under PCT Rule 13.1. In order for all inventions to be examined, the appropriate additional examination fees must be paid.

Group I, claim(s) 1-2 and 58-62, drawn to use with metadata streams with respect to a video stream.

Group II, claim(s) 3-8 and 63-65, drawn to thumbnail images in storing and managing digital media files.

Group III, claim(s) 9-15, drawn to vocabulary file of words keyed to the digital media records.

Group IV, claim(s) 16-17, drawn to right management.

Group V, claim(s) 18-23, 30-35, and 45-57, drawn to search engine searching digital media records.

Group VI, claim(s) 24-29 and 36-44, drawn to a statistical clustering algorithm in searching digital media records.

The inventions listed as Groups I-VI do not relate to a single general inventive concept under PCT Rule 13.1 because, under PCT Rule 13.2, they lack the same or corresponding special technical features for the following reasons: the special technical feature of each Group is mentioned above. Since the special technical feature of each one of Groups is not present in the other Groups, unity of invention is lacking.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)